

## MATERIAL SAFETY DATA SHEETS

MSDS No: **75-43-4**

Date: 07/08/2008

**SUPPLIER ADDRESS:** 6141 Easton Road, Bldg. 1  
PO Box 310  
Plumsteadville, PA 18949-0310

**EMERGENCY PHONE NUMBER:**

(215) 766-8861

### 1. CHEMICAL PRODUCT

PRODUCT NAME: **DICHLOROFLUOROMETHANE** SYNONYMS: Dichloromonofluoromethane, Freon 21, Halocarbon 21

### 2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS #	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
DICHLOROFLUOROMETHANE	CHCL2F	75-43-4	99+%	10	1000	10	NE

Note: NE = NONE ESTABLISHED

S/A = SIMPLE ASPHYXIAN

### 3. HAZARD IDENTIFICATION

\* \* \* EMERGENCY OVERVIEW \* \* \*

Liquid and gas under pressure.  
Can cause rapid suffocation.  
May cause frostbite.

### POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation, Skin

ACUTE EFFECTS: Mixture acts as a simple asphyxiant by displacing air necessary for life. Symptoms include lightheadedness, giddiness, disorientation, shortness of breath and possible cardiac arrhythmias. Pressure drop through valves and piping may cause extreme cold and frostbite on contact.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US ONLY):

NTP - No

IARC MONOGRAPHS - No

OSHA REGULATED - No

### 4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: Immediately flush with copious amounts of water for at least 15 minutes.

SKIN CONTACT: Immediately flush with copious amounts of water for at least 15 minutes while removing contaminated clothing. If frostbite occurs, flush affected areas with lukewarm water.

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

## 5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Ap

FLAMMABLE LIMITS: Nonflammable

LOWER:

UPPER:

EXTINGUISHING MEDIA: Use what is appropriate for surrounding fire.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. Move cylinders away from fire if this can be done safely.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions. Emits toxic fumes under fire conditions.

## 6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Position leaking cylinder with the leak at the top so that gas rather than liquid escapes.

SPECIALIZED EQUIPMENT: None

## 7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders. Use only in a well-ventilated area.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use. Store away from heat, flame, and sparks.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentration below exposure limits.

EYE / FACE PROTECTION: Goggles. A safety shower and eyewash station should be readily available.

SKIN PROTECTION: Protective gloves to prevent contact with cold equipment.

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Slight ethereal odor.

PHYSICAL PRESSURE: Gas

VAPOR PRESSURE: 1195 mm Hg @ 20 deg.C

VAPOR DENSITY (AIR=1): 3.57

BOILING POINT (C): 8.9

SOLUBILITY IN WATER: 1.77 wt.% @ 28 deg.C

SPECIFIC GRAVITY (H2O=1): 1.376 @ 20 deg.C

EVAPORATION RATE: Rapid

ODOR THRESHOLD: N/Av

## 10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Exposure to heat, ignition sources, and incompatibles.

MATERIALS TO AVOID: Alkali or alkaline earth metals, aluminum. Reacts violently with potassium and sodium. Oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Toxic carbon monoxide and carbon dioxide. Hydrochloric acid, hydrofluoric acid, toxic fumes of phosgene, and fluorides.

## 11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC50): 99,800 ppm, Rat 1 hour

LETHAL DOSE 50 (LD50): N/Av

TERATOGENICITY: N/Av

REPRODUCTIVE EFFECTS: N/Av

MUTAGENICITY: N/Av

## 12. ECOLOGICAL INFORMATION

This material is a Class 2 ozone depleting material.

## 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or

exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

#### 14. TRANSPORT INFORMATION

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Dichlorofluoromethane  
HAZARD CLASS: 2.2 (nonflammable gas)  
IDENTIFICATION NUMBER: UN1029  
REPORTABLE QUANTITIES: None  
LABELING: NONFLAMMABLE GAS

ADR / RID (EU Only): Class 2,2 A

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

#### 15. REGULATORY INFORMATION

OSHA: Process Safety Management: Materials are not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemicals.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: 200-869-8

NUMBER IN ANNEX 1 OF DIR 67/548: Not listed in annex 1.

EU CLASSIFICATION: N/Av

R: N/Av

S: N/Av

#### 16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS: N/Ap - Not Applicable N/Av - Not Available SA - Simple Asphyxiant NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.

## SPECIFICATION:

<b>CAS No.</b>	<b>75-43-4</b>
<b>Chemical Name:</b>	<b>Dichloromonofluoromethane</b>
<b>Synonyms:</b>	f21;AF22;F 21;f-21;fc21;CFC21;FC 21;fc-21;CHFC12;CHCl2F
<b>CBNumber:</b>	CB8724331
<b>Molecular Formula:</b>	CHCl2F
<b>Formula Weight:</b>	102.92
<b>MOL File:</b>	<a href="#">75-43-4.mol</a>

### Dichloromonofluoromethane Property

<b>mp :</b>	-135°C
<b>bp :</b>	8.9°C
<b>density :</b>	1,354 g/cm <sup>3</sup>
<b>NIST Chemistry Reference:</b>	<a href="#">Methane, dichlorofluoro-(75-43-4)</a>
<b>EPA Substance Registry System:</b>	<a href="#">Methane, dichlorofluoro-(75-43-4)</a>